

## LUBRICANT

Item		Capacity			Classification
		Liters	U S qts	Imp. qts	
Manual transmission oil					
2W D	G57	2.2	2.3	1.9	API GL-4 or GL-5 SAE 75W-90
	R 150	3.0	3.2	2.6	API GL-4 or GL-5 SAE 75W-90
4WD	G58	3.9	4.1	3.4	API GL-4 or GL-5 SAE 75W-90
	R 150F	3.0	3.2	2.6	
Automatic transmission fluid					ATF DEXRON 11
A43D	Dry fill	6.5	6.9	5.7	
	Drain and refill	2.4	2.5	2.1	
A340E	Dry fill	7.2	7.6	6.3	
	Drain and refill	1.6	1.7	1.4	
A340H					
(Transmission)	Dry fill	10.3	10.9	9.1	
	Drain and refill	4.5	4.8	4.0	
(Transfer)	Dry fill	1.1	1.2	1.0	
	Drain and refill	0.8	0.8	0.7	
A340F	Dry fill	7.6	8.0	6.7	
	Drain and refill	1.6	1.7	1.4	
Transfer oil	W56 (RF 1 A)	1.6	1.7	1.4	API GL-4 or GL-5
	G 58, R 150F, A340F (VF 1 A)	1.1	1.2	1.0	SAE 75W-90
Differential oil					Standard differential
2WD	7.5 in.	1.35	1.4	1.2	API GL-5 hypoid gear oil
	8.0 in. 2 pinion	1.8	1.9	1.6	Above -18°C (0°F)
	4 pinion	2.2	2.3	1.9	SAE 90
4WD	Front Standard differential	1.6	1.7	1.4	Below -18°C (0°F)
	A.D.D.	1.86	2.0	1.6	SAE 80W-90 or 80W
	Rear	2.2	2.3	1.9	A.D.
					D. (4WD Front only)
					TOYOTA "GEAR OIL SUPER" oil or hypoid gear oil API GL-5 SAE 75W-90
Steering gear box oil					API GL-4, SAE 90
	2W D	380 - 400 cc 23.2 - 24.4 cu in.			
	4WD	400 cc	24.4 cu in.		

**LUBRICANT (Cont'd)**

Item	Capacity			Classification
	Liters	US qts	Imp. qts	
Power steering fluid				ATF DEXRON <sup>®</sup> 11
Pump	<b>300 cc</b>	<b>18.3 cu in.</b>		
Total	<b>900 cc</b>	<b>54.9 cu in.</b>		
Ball joint grease (2WD)		–		Molybdenum disulphide lithium base, NLG I No. 1 or No. 2
Chassis grease (4WD)				Lithium base, NLG I No. 2 Molybdenum disulphide lithium base, NLG I No. 2
Propeller shaft (Except double cardan joint)		–		
Double cardan joint				
Wheel bearing grease		–		Lithium base multipurpose, NLG I No. 2
Steering knuckle and front axle shaft grease (4WD)		–		Molybdenum disulphide lithium base, NLG I No. 2
Brake fluid		–		SAE J 1703 or FMVSS No. 116 DOT 3